

# Terra X



Disc Harrow



Kongskilde Terra X Disc Harrow



Double taper roller bearings

### Double taper roller bearings

The heavy-duty double taper roller bearing units with increased sealing protection can withstand the high load demands of the machine with a minimum of wear and maintenance.



Scalloped discs

### Scalloped discs

The Terra X disc harrow is equipped with 660 mm scalloped discs manufactured from high quality steel. The discs are fitted on a 40 mm square shaft.

The X-pattern of the disc shafts provides an even finish in all types of terrain and varying soil conditions.

### Standard:

- Scalloped 660 mm discs
- Hydraulically adjustable working angle from 0° - 25°
- Double taper roller bearings
- 40 mm shaft
- The main frame can be filled with water
- Vertical hydraulic fold
- Adjustable working depth (with rear cage roller)
- Rear cage roller Ø 550/630 mm

### Technical Data

Model	Working width	Transport width	Number of discs	Bearing units	Weight w/o roller	Recommended Tractor power
Terra-X 300	3,0 m	3,0 m	24	8	2.375 kg	90-120 HP
Terra-X 400	4,0 m	3,0 m	32	8	2.550 kg	100-130 HP
Terra-X 450	4,5 m	3,0 m	36	8	2.570 kg	110-150 HP
Terra-X 4000	4,0 m	3,0 m	32	8	3.470 kg	120-200 HP
Terra-X 5000	5,0 m	3,0 m	40	8	4.340 kg	160-260 HP
Terra-X 6000	6,0 m	3,0 m	48	16	4.860 kg	180-300 HP
Terra-X 7000	7,0 m	3,0 m	56	16	5.540 kg	200-350 HP



Kongskilde Industries A/S

Tel. +45 33 68 35 65

mail@kongskilde.com

www.kongskilde.com